



Anti-fog

Sporty style

Scratch resistant

EN 166:2001 Compliant

Light and comfortable





In comparison to standard plastic, polycarbonate lenses are thinner and light, offer inherent UV protection, and offer a greater impact resistance than common plastics.

| Features  | Clear | Grey | Indoor/<br>Outdoor | Blue<br>Mirror | Clear AF |
|---|-------|------|--------------------|----------------|----------|
| Polycarbonate lenses                                      | ☑     | ☑    | ☑                  | ☑              | ☑        |
| Optically correct   | ☑     | ☑    | ☑                  | ☑              | ☑        |
| Light and comfortable                                     | ☑     | ☑    | ☑                  | ☑              | ☑        |
| Specifically designed for outdoor applications            |       | ☑    |                    |                |          |
| Specifically designed for indoor and outdoor applications |       |      | ☑                  |                |          |
| Impact resistant  | ☑     | ☑    | ☑                  | ☑              | ☑        |
| Excellent orbital eye coverage                            | ☑     | ☑    | ☑                  | ☑              | ☑        |
| Sporty style  | ☑     | ☑    | ☑                  | ☑              | ☑        |
| Anti-scratch  | ☑     | ☑    |                    |                | ☑        |

| Product Code | Product Description | Gross Weight | Box dimensions (W x L x H in cm) | Case Qty |
|--------------|---------------------|--------------|----------------------------------|----------|
| AZ250        | Orb Clear           | 12           | 81 x 59 x 26                     | 300      |
| AZ251        | Orb Grey            | 12           | 81 x 58 x 26                     | 300      |
| AZ252        | Orb Indoor/Outdoor  | 12           | 80 x 58 x 26                     | 300      |
| AZ253        | Orb Blue Mirror     | 12           | 81 x 60 x 26                     | 300      |
| AZ265        | Orb Clear Full      | 12           | 80 x 58 x 25                     | 300      |

ANSI Z87.1-2010 | EN 166:2001